

Dental Air Compressor System

Oil-less Air System Tank Mounted with Twin Tower Desiccant Air Dryers

Key Advantage

- Ultra-low dew point, dew point down to -40°C protects equipment
- Dew Point monitoring with digital reading
- Digital pressure reading and setting on keypad for optimal operation
- 2 stages condensation removal
- Completely oil-less, no contamination from compressor operation
- Low Maintenance Cost
- Fewer moving parts, no oil change needed
- Easy to Install
- Compact design with single point connection
- Energy Efficient
- Industrial grade parts



Options

- Value model – moisture indicator with pressure switch start stops**

Models

Model	User	# of Compressor	HP	Tank (gal.)*	Voltage*
AT1DA11-HT-012HT-007RD	1-2	1	0.75	12	230V/1Ph +/-10%
AT2DA11-HT-012HT-007RD	3-5	2	1.5	12	
AT3DA11-HT-030HT-007RD	5-7	3	2.25	30	
AT1DA11-HT-060HT-030SC	7-10	1	3	30	230V/1Ph
AT1DA11-HT-060HT-050SC	10-14	1	5	30	230V/3ph
AT1DA11-HT-060HT-075SC	15-20	1	7.5	30	460V/3ph 575V/3ph

*Other built options are available

**Available for RD model only

Website: www.3dproto.ca

Email: sales@3dproto.ca

